

**Product name : SOLIDWAXCLASSIC****XD 4060****Description**

SolidWax has been formulated for the maintenance of wooden surfaces treated with Solid range water-based products.

**Version**

XD 4060 SolidWaxClassic gloss effect

**Application possibilities**

It can be used for the maintenance of wooden surfaces treated with Solid range water-based products.

**Peculiarities**

It is a water-based emulsion wax. It contains no dangerous substances for people and nature. It preserves wooden surfaces and brightens up the floor.

**Application instructions**

Cloth, cloth for waxing

**Chemical and physical characteristics at 23° C**

Appearance	Yellowish liquid
pH	8 +/- 1

**Surface preparation**

For a daily maintenance.

Clean the floor as described on SolidClean technical sheet; floor must be completely dry before wax application. Dilute SolidWax with 20% of water and apply with a cloth damped with SolidWax and squeezed. Let the floor dry. It is not necessary to rinse or polish. Once dry, it is possible to walk on the floor.

For a particular maintenance due to wear.

Proceed as described before. Dilute SolidWax with 50% of water and apply it with a cloth for waxing damped with SolidWax and squeezed. Carefully spread the product on the whole surface. Let the floor dry. It is not necessary to rinse or polish. Once dry, it is possible to walk on the floor.

**Package**

5 L tanks.

**Storage**

The product keeps unaltered its characteristics throughout 18 months if stored inside its original package, tightly closed, at 23° C. Do not store in damp or wet places at temperatures exceeding 35° C.

**Packaging recycling**

The plastic package must be recycled in the right dumper or recycling point (according to the local garbage collection). Please, check if the package is empty and dry, with the minimum possible product quantity inside.



YouTube



---

### Warnings

Data and information inside this Technical Sheet represent our current best knowledge and experiences and cannot be used as a warranty due to the diversity of materials existing on the market and the difficult monitoring of application conditions.

The final user must check if the product corresponds to his own needs in relation to application tools, supports and environmental conditions of application and drying. In any case, Renner Italia S.p.A. guarantees the constant quality of its products. Renner Italia S.p.A. reserves the right to modify and update this technical sheet according to its own needs. Customers shall verify to own the updated version of this sheet.

**CAREFULLY READ AND UNDERSTAND THIS TECHNICAL SHEET BEFORE USING THE PRODUCT**

